

100WVDC AND UNDER

(pF)

Diameter dØ ± 1m/m	Temperature Characteristic			
	Y5F	Y5P	Z5U	Z5V
4	100 - 470	200 - 1000	1000 - 2700	1000 - 5000
5	500 - 680	1200 - 1500	3000 - 3900	5600 - 8200
6	820 - 1000	1800 - 2200	4000 - 5600	10000
8	1200 - 2700	2500 - 5600	6800 - 10000	22000 - 33000
10	3000 - 5600	6200 - 10000	22000 - 100000	40000 - 100000

500WVDC

Diameter dØ ± 1m/m	Temperature Characteristic			
	Y5F	Y5P	Z5U	Z5V
5	100 - 330	200 - 560	1000 - 3000	2000 - 3300
6	350 - 500	620 - 1000	3300 - 3900	3900 - 4700
8	560 - 1200	1200 - 2200	4700 - 6800	5000 - 8200
10	1500 - 2200	2500 - 3900	8200 - 10000	10000 - 15000
12	2500 - 3300	4000 - 5600	12000 - 15000	20000
14	2500 - 5000	6200 - 10000	18000 - 33000	22000 - 50000

1000WVDC

Diameter dØ ± 1m/m	Temperature Characteristic			
	Y5F	Y5P	Z5U	Z5V
5	100 - 220	100 - 500	500 - 1200	1000 - 2200
6	250 - 500	560 - 1000	1500 - 2200	2500 - 3300
8	560 - 1200	1200 - 2000	2500 - 5000	3500 - 5600
10	1500 - 2000	2200 - 3300	5000 - 8200	6200 - 10000
12	2200 - 3000	3500 - 5000	10000 - 12000	
14	3300 - 3900	5600 - 6800	15000 - 18000	
16	4200 - 5600	7200 - 10000	20000 - 22000	

Voltages values for sizes of TC not listed above, consult Factory or Area Representative.